

Modular Air Cooled Chiller (No Tank and Pump)

Standard Features

- Heavy duty welded, tubular steel frame with high gloss powder coat finish and laminated polyethylene cabinet
- U.L. Listed, and EPA Compliant, eco-friendly R410a refrigeration condensing unit
- Single refrigeration circuit with Copeland scroll compressor with crankcase heater
- Air cooled, high ambient, vertical discharge, condensers for 100°F ambient with fan cycle control
- Weather proof electrical panel with single point power connection and 24 vac control circuit
- Remote control panel for indoor installation provides lighted on/off switches and digital thermostat
- Stainless steel brazed plate evaporator with low pressure compressor interlock safety
- Auto reset low pressure safety; manual reset high pressure safety
- Externally equalized thermal expansion valve, liquid line filter drier, and sight glass
- Low water flow compressor interlock safety locks out compressors in low flow condition
- Non-ferrous water lines with FPT connections insulated with 1/2" closed cell insulation
- Warranty: one (1) years limited parts, five (5) years limited compressor warranty
- Systems leak checked, pressure tested, run tested under load and shipped operation ready

Options & Accessories

- Receivers for 90% refrigerant storage (heated and insulated for temperatures below 30°F ambient)
- Condenser coil coating for corrosion protection in coastal areas
- Fan speed control to maintain steady head pressure in cold ambient
- Voltage and phase monitor in 2 through 7.5 ton
- Cabinet mounted glycerin filled fluid supply pressure gauge
- Cabinet mounted, glycerin filled refrigeration pressure gauges
- Cabinet mounted, analog fluid inlet and outlet gauges
- Inhibited propylene glycol concentrate or 65% / 35% premix in 55 gallon drums or 5 gallon carboys
- Castors for portability
- Factory authorized technician for startup and training



Physical Data	
Dimensions:	35" L x 35" W x 51"H
Ship Weight:	520 lbs.
Minimum Clearances:	30" All Sides 120" above Top
Noise Rating:	77 dBA @ 10 feet
Fans CFM:	3570 cfm @ 125°F
Tank Capacity:	None
Connections:	.1.0" FPT CHWS and CHWR

Electrical Data		
Power Supply: 208-230/3/60		
Compressors:	LRA:	1 @ 95 Amps
	RLA:	14.1 Amps
Fan Motors:	FLA:	1 @ 1.2 Amps
Total Circuit:	FLA:	15.3 Amps
	MCA:	19 Amps
	MOP:	30 Amps