

## Air Cooled Package Chiller With Tank and Pump

### Standard Features

- Heavy duty welded, tubular steel frame with high gloss powder coat finish and laminated polyethylene cabinet
- U.L. Listed, and EPA Compliant, eco-friendly R410a refrigeration condensing unit
- Single refrigeration circuit with Copeland scroll compressor with crankcase heater
- Air cooled, high ambient, vertical discharge, condensers for 100°F ambient with fan cycle control
- Weather proof electrical panel with single point power connection and 24 vac control circuit
- Remote control panel for indoor installation provides lighted on/off switches and digital thermostat
- High performance coaxial evaporator with inner copper tubing and protective steel shell. UL and ASME listed coil is insulated against condensation with expanded foam
- Auto reset low pressure safety; manual reset high pressure safety
- Externally equalized thermal expansion valve, liquid line filter drier, and sight glass
- Low water flow compressor interlock safety locks out compressors in low flow condition
- Non-ferrous water lines with FPT connections insulated with 1/2" closed cell insulation
- 26 gallon, high density, polyethylene reservoir insulated with 1/2" closed cell insulation
- High head centrifugal process pump rated at 40 psi at 2.5 GPM/ton
- Warranty: one ( 1 ) years limited parts, five ( 5 ) years limited compressor warranty

### Options & Accessories

- Receivers for 90% refrigerant storage (heated and insulated for temperatures below 30°F ambient)
- Condenser coil coating for corrosion protection in coastal areas
- Fan speed control to maintain steady head pressure in cold ambient
- Cabinet mounted glycerin filled fluid supply pressure gauge
- Cabinet mounted, glycerin filled refrigeration pressure gauges
- Cabinet mounted, analog fluid inlet and outlet gauges
- Inhibited propylene glycol concentrate or 65% / 35% premix in 55 gallon drums or 5 gallon carboys
- Castors for portability
- Factory authorized technician for startup and training



Electrical Data		
<b>Power Supply:</b> 460/3/60		
<b>Compressors:</b>	LRA:	2 @ 75 Amps
	RLA:	2 @ 10.6 Amps
<b>Fan Motor:</b>	FLA:	2 @ 2.8 Amps
<b>Pump Motor:</b>	H.P.	1.5
	FLA:	3.0 Amps
<b>Total Circuit:</b>	FLA:	27.0 Amps
	MCA:	33.8 Amps
	MOP:	35 Amps

Physical Data	
<b>Dimensions:</b>	66"L x 44"W x 74"H
<b>Ship Weight:</b>	1575 lbs.
<b>Minimum Clearances:</b>	30" All Sides 60" above Top
<b>Noise Rating:</b>	88 dBA @ 10 feet
<b>Fans CFM:</b>	8000 cfm @ 125°F
<b>Tank Capacity:</b>	100 Gal. ( Atmospheric )
<b>Connections:</b>	1.25" FPT CHWS and CHWR