

Model No.	Rated Tons RT	Weights (lbs)		Piping Connections (In.)						Fan Motor H.P.	Fan Dia. (Inch)	Air Flow (cfm)	Nom. Flow (gpm)
		Dry Wt.	Wet Wt.	In	Out	O	Dr	Float	Q				
¹ ACTS-5	3.3	86	251	1-1/2	1-1/2	1	3/4	1/2	-	1/6*	19 1/2	2,118	10
¹ ACTS-8	5.3	93	262	1-1/2	1-1/2	1	3/4	1/2	-	1/6*	19 1/2	2,648	16
¹ ACTS-10	6.7	123	443	1-1/2	1-1/2	1	3/4	1/2	-	1/4*	26 3/8	3,531	20
¹ ACTS-15	10.0	139	536	2	2	1	1	1/2	-	1/4*	26 3/8	4,767	30
³ ACTS-20	13.3	190	719	2	2	1	1	1/2	-	1/2 ¹	30 1/4	6,356	40
² ACTS-25	16.6	227	887	2-1/2	2-1/2	1	1	1/2	-	3/4 ²	30 1/4	7,000	50
² ACTS-30	20.3	253	1074	2-1/2	2-1/2	1	1	1/2	-	1.0 ²	30 1/4	8,100	61
² ACTS-40	27.7	369	1133	2-1/2	2-1/2	1	1	3/4	-	1-1/2 ²	38 1/4	9,800	83
² ACTS-50	35.0	435	1313	3	3	1	1	3/4	-	1-1/2 ²	38 1/4	11,500	105
² ACTS-60	41.7	504	1472	3	3	1	1	3/4	-	1-1/2 ²	46	14,700	125
² ACTS-70	48.3	610	1555	4	4	1	1	3/4	-	1-1/2 ²	46	17,500	145
² ACTS-80	56.0	642	1588	4	4	1	1	3/4	-	2 ²	46	18,900	168
² ACTS-100	69.3	887	2361	4	4	1	1	1	-	3 ²	57 7/8	24,500	208
² ACTS-125	87.3	1025	2983	5	5	2	1	1	-	3 ²	57 7/8	29,060	262
² ACTS-150	106.0	1375	5731	6	6	2	2	1	-	5 ²	68 7/8	33,260	318
² ACTS-175	123.0	1569	5887	5	5	2	2	1	-	5 ²	68 7/8	40,250	369
² ACTS-200	142.0	1914	7612	6	6	2	2	1 1/4	1-1/4	5 ²	68 7/8	43,760	426
² ACTS-225	153.3	2112	7744	6	6	2	2	1 1/4	1 1/4	7 1/2 ³	93	61,270	460
² ACTS-250	173.3	2266	7854	8	8	2	2	1 1/4	1 1/4	7 1/2 ³	93	61,270	520
² ACTS-300	206.7	2823	9995	8	8	2	2	1 1/4	1 1/4	10 ³	93	77,020	620
² ACTS-350	248.0	2996	10164	8	8	2	2	1 1/4	1 1/4	10 ³	93	77,020	744
² ACTS-400	281.7	4776	14984	8	8	4	2	2	2	15 ³	117	91,030	845
² ACTS-500	371.0	5342	15550	10	10	4	2	2	2	15 ³	117	91,030	1113
² ACTS-600	426.0	7401	23637	10	10	4	2	2	2	20 ³	133 1/8	125,000	1278
² ACTS-700	516.0	7848	24127	10	10	4	2	2	2	20 ³	133 1/8	125,000	1548
² ACTS-800	567.7	9636	26356	12	12	4	3	2	2	30 ³	141	175,000	1703
² ACTS-1000	751.0	10199	27359	12	12	4	3	2	2	30 ³	141	175,000	225.53

Model No. (Tons)	Dimensions (ins)									Anchor		Req'd. Pump Head
	Height	Dia.	D1	W	B	A	h	h'	C	Size (ins)	Length (ins)	
ACTS-5	52	34	21-5/8	18 3/4	8	-	6		-	1/2	4 3/4	5.0
ACTS-8	56	34	21 5/8	18 3/4	8	-	6		-	1/2	4 3/4	5.0
ACTS-10	54	42	29 1/2	25 5/8	8	-	6		-	1/2	4 3/4	5.0
ACTS-15	59	46	34 5/8	30	8	-	6		-	1/2	4 3/4	5.3
ACTS-20	63	55	44	38 1/4	8	-	6		-	1/2	4 3/4	5.6
ACTS-25	71	55	44	38 1/4	8	-	6		-	1/2	4 3/4	5.6
ACTS-30	69	62	52 1/2	37	8	-	6		-	1/2	4 3/4	6.0
ACTS-40	75	72	57 7/8	40 7/8	10	-	8		-	1/2	4 3/4	6.6
ACTS-50	75	79	66 1/8	46 3/4	10	-	8		-	1/2	3 3/4	6.6
ACTS-60	75	79	66 1/8	46 3/4	10	-	8		-	1/2	4 3/4	6.6
ACTS-70	80	86	69 3/8	34 1/2	10	-	8	9 1/2	10	1/2	4 3/4	6.6
ACTS-80	80	86	69 3/8	34 1/2	10	-	8	9 1/2	10	1/2	4 3/4	6.6
ACTS-100	87	120	92 1/2	46 1/4	12	-	12	14	12	5/8	8	8.2
ACTS-125	90	130	103 1/8	51 1/2	12	-	12	14	12	5/8	8	10.0
ACTS-150	98	130	112 1/2	56 1/4	12	-	12	13 1/2	16	5/8	8	10.0
ACTS-175	98	130	112 1/2	56 1/4	12	-	12	13 1/2	16	5/8	8	11.0
ACTS-200	118	149	132	93 3/8	12	5 1/8	12	16	23	5/8	8	11.0
ACTS-225	125 5/8	148 3/8	132	93 3/8	12	5 1/8	12	16	23	5/8	8	11.0
ACTS-250	125 5/8	148 3/8	132	93 3/8	12	5 1/8	12	16	23	5/8	8	12.0
ACTS-300	131 7/8	174 3/4	156 1/8	110 3/8	12	5 1/2	12	16	23	5/8	8	12.0
ACTS-350	133 1/2	188 5/8	169 1/8	119 5/8	12	5 1/2	12	16	23	5/8	8	13.2
ACTS-400	153 1/2	203 7/8	200 3/4	100 3/8	20	5 1/2	12	16	31 1/2	3/4	8	13.2
ACTS-500	154 11/16	219 5/8	216 1/2	108 1/4	20	5 1/2	12	16	31 1/2	3/4	8	13.2
ACTS-600	171 5/8	259 7/8	255 1/8	97 5/8	20	5 1/2	12	16	31 1/2	3/4	8	16.4
ACTS-700	181 5/16	259 7/8	255 1/8	97 5/8	20	5 1/2	12	16	31 1/2	3/4	8	18.2
ACTS-800	194 11/16	299 1/4	295 1/4	113	20	5 1/2	12	16	31 1/2	3/4	8	20.0
ACTS-1000	202 1/2	299 1/4	295 1/4	113	20	5 1/2	12	16	31 1/2	3/4	8	20.0